

AMENDMENTS TO THE CLAIMS

1. (Currently amended) An image pick-up device comprising:
a main body;
a camera for taking a picture; and
a display device displaying a ~~taken~~-picture taken from the perspective of the camera and
arranged at a surface of said main body on the same side as said camera, wherein
said camera is fixed to said main body such that an optical axis of said camera extends in
a direction different from a direction perpendicular to a display surface of said display device.
2. (Original) The image pick-up device according to claim 1, wherein
said camera is arranged on one side of the vertically opposite sides of said display device,
and the optical axis of said camera is inclined toward the other side.
3. (Original) The image pick-up device according to claim 1, wherein
said camera is arranged on one side of the laterally opposite sides of said display device,
and the optical axis of said camera is inclined toward the other side.
4. (Original) The image pick-up device according to claim 1, wherein
said display device is a main display portion arranged on one of opposite surfaces of said
main body,
said image pick-up device further comprises a sub-display portion arranged on the other
surface of said main body, and
said camera and said main display portion are arranged on said one of the opposite
surfaces of said main body.
5. (Original) The image pick-up device according to claim 1, further comprising:
a main display portion arranged on one of opposite surfaces of said main body; wherein
said display device is a sub-display portion arranged on the other surface of said main body, and
said camera and said sub-display portion are arranged on said other surface of said main body.

6. (Original) The image pick-up device according to claim 1, wherein
said main body has a structure formed of first and second bodies foldably coupled
together, and
said camera and said display device are arranged on said first body.

7. (Original) The image pick-up device according to claim 1, wherein
said main body has a structure formed of first and second bodies foldably coupled
together, and
said display device is arranged on said first body, and said camera is arranged on said
second body.

8. (Original) The image pick-up device according to claim 1, wherein
said main body has a structure formed of a single body.

9. (Original) The image pick-up device according to claim 1 further comprising:
an additional camera arranged on said main body, wherein
said main body has a structure formed of first and second bodies foldably coupled
together, and
said camera is arranged on one of said first and second bodies, and said additional camera
is arranged on the other of said first and second bodies.

10. (Original) The image pick-up device according to claim 1 further comprising:
an additional camera arranged on said main body, wherein
said main body has a structure formed of first and second bodies foldably coupled
together, and
said camera and said additional camera are arranged on one of said first and second
bodies.

11. (Original) The image pick-up device according to claim 10, wherein

said camera and said additional camera are arranged on the different surfaces of one of said first and second bodies, respectively.

12. (Original) The image pick-up device according to claim 11, wherein
said additional camera has an optical axis perpendicular to the display surface of said display device, and

said camera has an optical axis in a direction different from a direction perpendicular to the display surface of the display device.

13. (Original) The image pick-up device according to claim 10, wherein
said camera and said additional camera are both arranged on the same side of said one of the bodies.

14. (Original) The image pick-up device according to claim 13, wherein
one of said camera and said additional camera is arranged on one of the vertically opposite sides of said display device, and has an optical axis inclined toward the other side of said vertically opposite sides, and

the other of said camera and said additional camera is arranged on one of the laterally opposite sides of said display device, and has an optical axis inclined toward the other side of said laterally opposite sides.

15. (Previously presented) An image pick-up device comprising:
a main body having a first side and a second side;
a camera for taking a picture fixed to said main body first side and having an optical axis;
and

a first display device including a display surface displaying a picture taken by said camera and arranged on said first side;

wherein said optical axis extends in a direction different from a direction perpendicular to said display surface.

16. (Previously presented) The image pick-up device according to claim 15, wherein said first display device includes first and second vertically opposite sides and said camera is arranged on one of said first and second vertically opposite sides, and the optical axis of said camera is inclined toward the other of said first and second vertically opposite sides.

17. (Previously presented) The image pick-up device according to claim 15, wherein said first display device includes first and second laterally opposite sides and said camera is arranged on one of said first and second laterally opposite sides, and the optical axis of said camera is inclined toward the other of said first and second laterally opposite sides.

18. (Previously presented) The image pick-up device according to claim 15, further comprising a second display device on the second side of said main body.

19. (Previously presented) The image pick-up device according to claim 18, wherein said first display device comprises a main display portion and said second display device comprises a sub-display portion.

20. (Previously presented) The image pick-up device according to claim 18, wherein said first display device comprises a sub-display portion and said second display device comprises a main display portion.